


CUBE2

Project Name:	
Type:	



APPLICATION

These color capable luminaires bring flexibility and open doors to various types of applications. The RGB technology is a combination of three primary colors - red, green, and blue - to form a different array of colors. The RGBW technology is a combination of those three primary colors in addition to white. Additional white LEDs illuminates a much purer white tone and brings flexibility for color mixing through the RGB chips. Playing with different colors of the LEDs can form infinite color hue possibilities to not only just illuminate space, but manipulate for your desired hue and shades. Flexible control solutions from wireless remote, Bluetooth, to DMX512 with a wall mount touch panel can provide an ultimate solution to optimize the needs from residential to commercial, healthcare, education, retails, entertainment, office, and more.

MOUNTING:


- Pendant, surface and wall mount.
- Recessed mount including T-bar, Screw slot and Drywall.

FINISH:

- Standard powder-coat textured white paint finish on exposed trim.
- Consult factory for custom colors.
- Comes with snap-in acrylic lens as standard.

LISTING:

- UL /cUL listed.
- Listed to UL 1598 and UL 8750
- UL listed for dry & damp location
- Assembled in USA.
- Warranty:
 - Power Supply:** 5 years limited warranty.
 - DMX:** 3 years limited warranty.
 - LED:** 3 years limited warranty.



Specifications: CUBE2

Width: 2.5 (64)
Depth: 4 (101)

All dimensions are in inches (millimeters).

WEIGHT

Item	lbs	kg
CUBE 2 2FT PENDANT	6.76	3.07
CUBE 2 3FT PENDANT	8.91	4.04
CUBE 2 4FT PENDANT	10.78	4.89
CUBE 2 8FT PENDANT	19.71	8.94
CUBE 2 HC90 PENDANT	15.19	6.89
CUBE 2 X PENDANT	15.08	6.84
CUBE 2 T PENDANT	10.45	4.74
CUBE 2 2FT DRYWALL	8.14	3.69
CUBE 2 3FT DRYWALL	11.00	4.99
CUBE 2 4FT DRYWALL	12.89	5.85
CUBE 2 8FT DRYWALL	25.45	11.55
CUBE 2 4FT G1	12.85	5.83
CUBE 2 8FT G1	23.73	10.77
CUBE 2 4FT SS	12.05	5.47
CUBE 2 8FT SS	22.15	10.05
CUBE 2 HC90 DRYWALL	17.37	7.88
CUBE 2 X DRYWALL	17.63	8.00
CUBE 2 T DRYWALL	12.76	5.79

CUBE2

ORDERING INFORMATION * These custom products are non-cancellable, non-returnable, and non-refundable with the exception of manufacturer defects or damages. **EXAMPLE:** CUBE2-IND-4-DLO-RGBW-40K-UNV-CV24-BLT

MODEL	ROW ¹	SECTION ²	LED Downlight (per/4ft section)	LED Uplight (per/4ft section)	SYSTEM
CUBE2-IND (Individual Mount)	xx' Specify nominal overall row length in 1' increments (Continuous runs)	2 2' Length	(Blank) DLO DHO No Downlight ¹⁴ Low output, 9.3W/ft High output, 18.6W/ft	(Blank) ULO No Uplight Low output, 9.3W/ft	RGBW-30K RGBW-40K RGBW with wireless or Bluetooth solution, 3000K white ^{4, 13} RGBW with wireless or Bluetooth solution, 4000K white ^{4, 13}
CUBE2-CON (Continuous Row Mount)		3 3' Length			
		4 4' Length			
		6 6' Length 8 8' Length ³			
CUBE2-SQ (Square)	X'-Y' Specify dimension in inches. (Minimum required dimension is 2'-2") Must provide a sketch on the last page				
CUBE2-CM (Custom)		Must provide a sketch on the last page			

MOUNTING		VOLTAGE		FINISH		CORD FINISH ⁸		CEILING TYPE (for pendant)	
(Blank)	Pendant	UNV	120-277V	(Blank)	Matte White RAL #9003 (Std.)	(Blank)	White (Std.)	X1	T-bar ceiling
S	Ceiling Surface	120	120V	BK	Black RAL #9011	BK	Black	X2	Hard ceiling
W	Wall	277	277V	SV	Silver (Cardinal #T353-GR06)			X3	Sloped Hard ceiling
G1	9/16", 15/16", 1" T-bar Ceiling Grid ⁶			CC	Custom Color				
SS	Screw Slot Ceiling Grid			CSS	Custom Canopy Color (White is Std.)				
FT	Standard 1/2" Flange (Drywall) ^{5,7}								
SF	Spackle Flange (Trimless) ^{5,7}								

SUSPENSION LENGTH		LED DRIVER		CONTROLS ¹⁵	
AC48	Adjustable Aircraft Cable Canopy 48"L	CV24	24VDC Power Supply	WL-MZ-WH	4-Zone RF remote, white
AC96	Adjustable Aircraft Cable Canopy 96"L			WL-MZ-BK	4-Zone RF remote, black
ST24	Stem Canopy 24"L			BLT	Bluetooth / Smartphone App
ST48	Stem Canopy 48"L	4DMX	4-Channel DMX512 decoder ^{16, 19}	(Blank)	No options or controls from below
	* Contact factory for custom length. 1 pair (2 aircraft cables) standard for up to 8' length.			DMXT14	4-zone DMX512 wall mount touch panel, 85-265VAC input only
				DMXT8	4-zone DMX512 wall mount touch panel, 5vdc adapter provided

OPTIONS			
HC90-11	90° Horizontal Lit Connector, 1'x1' ⁹	CW90	Ceiling to Wall corner connector ¹¹
HC90-12	90° Horizontal Lit Connector, 1'x2' ⁹	WW	Wall Wash
HC90-21	90° Horizontal Lit Connector, 2'x1' ⁹	GLR	Fast Blow Fuse
HC90-22	90° Horizontal Lit Connector, 2'x2' ⁹	GMF	Slow Blow Fuse
HC135-22	135° Horizontal Lit Connector, 2'x2' ⁹	COC	Separated EM feed for City of Chicago code compliance
TC	T-Type Lit Connector ¹⁰	STB	Slip Through Bracket ¹²
XC	X-Type Lit Connector ¹⁰	DROP	1/2" drop lens
		UDSC	Up and Down separate control
		WL-HLD-WH	Remote holder for WL-MZ, white
		WL-HLD-BL	Remote holder for WL-MZ, black

NOTES:

- Specify only when Continuous Row Mount.
- No need to select, if same as row length and section length.
- Comes with 1pc 8ft lens.
- Custom wattage or lumen is not available.
- Requires # STB as standard.
- Compatible with T-bar ceiling type.
- Compatible with hard ceiling type.
- Black is not available for the EM option.
- Refer to a separate CUBE2-HC90 spec sheet to find more information.
- Cannot be ordered as wall mount.
- Only applicable for FT and SF mounting option.
- Standard with "FT" and "SF" mounting.
- Refer to RGBW chart (Table 4) to find more information.
- Downlight cover may ship separately depending on the configuration.
- Refer to Table 1 and Table 2 to find more information.

CUBE2

RGBW CONFIGURATION

Input Voltage	24V
Watt / foot	9.3 W/ft, 563 lm/W
Lumen / foot	R: 36.82 lm/ft
	G: 79.55 lm/ft
	B: 25.82 lm/ft
	W: 100.35 lm/ft (30K), 116.8 lm/ft (40K)
CRI for white LEDs	80
Color Consistency	3-step MacAdam binning
Lumen Maintenance	> 50,000 hours
Control Options	Wireless Easy control remote, Group / Multi Zone wireless remote, Bluetooth (Smartphone / APP)
Warranty	5 years limited warranty for power supply, 15 years limited warranty for LED source

CONTROL (TABLE 1)



* Remote holder sold separately

WL-MZ (RF remote control)

Dimensions	W 2" x D 0.825" x H 4.725"
Weight	0.1lbs
Signal Type	RF (Radio Frequency) 2.4GHz
Range	98ft from fixture open air
Zone / Mode	4 zones / 9 modes
Working Temp.	-4°F to 131°F (-20°C to 55°C)
* Battery	2 x AAA battery

* Not included



WL-HLD-WH



WL-HLD-BK



Smart Life




Tuya Smart

BLT (Bluetooth / Smartphone App)

	Bluetooth
Software	IOS 8.0 and up, Android 4.4 and up
App	Smart Life or Tuya Smart supported
Features	Group, Scenes
Bluetooth Distance	> 49ft in open area
Additional Feature	Home Management / Third party control -> Alexa, Google Assistant (by others)

CUBE2

4DMX (TABLE2)



4DMX (4-channel DMX decoder)

Dimensions	L 6.7" x W 2" x D 0.9"
Output Current	5A / channels
Input Voltage	12-24V DC
Output Power	4 x (60-120)W
Frequency	PWM output



DMXT14


Zone	4 zone
Signal	DMX512 protocol
Input Voltage	85-265VAC
Dimensions	L 3.4" x H 3.4" x D 1.45"
Features	10 built-in mode, scene
Operating Temp.	-22°F ~ 131°F (-30°C ~ 55°C)



DMXT8

Zone	4 zone
Signal	DMX512 protocol
Dimensions	L 7" x H 1.3" x D 1.9"
Features	12 built-in mode, scene
Operating Temp.	-22°F ~ 131°F (-30°C ~ 55°C)

ARCHITECTURAL LINEAR




CABLE

SURFACE

WALL


RECESSED

- MOUNTING DETAILS




*See a separate CUBE2-Recessed spec sheet to find detail information.

- LIT CONNECTOR




HC90-11
HC90-12
HC90-21
HC90-22

* See a separate CUBE2-HC90 spec sheet to find more information.




HC135-22

* See a separate CUBE2-HC90 spec sheet to find more information.



TC



XC

* See a separate CUBE2-T, CUBE-X spec sheet to find more information.

ARCHITECTURAL LINEAR

CUBE 2 LIT CONNECTOR PATTERNS

The lit connector system allows continuous illumination all the way through the corner section.

Instruction:

- Please provide sketches illustrating corner types, overall dimensions including corner dimensions, and locations required.
- HC90, TC, and XC connectors are 90 degree corners (overall, outside dimension).

