

APPLICATION

The Prismatic borosilicate glass lens compact wall pack is ideal for both commercial and residential applications with wall mounting.

FEATURES:

- Die-cast aluminum door frame with prismatic borosilicate glass lens.
- Door frame holds lens and seals housing gasket with stainless steel screws.
- Die-cast aluminum housing with 1/2" hub; button photocell can be field installed.
- Silicone rubber gasket between backplate and front cover for wet locations.
- Dark bronze finish is standard; white or black finish is also available.
- Optional photocell for dusk to dawn.

MOUNTING:

- Wall mounting only.
- Easily installed on recessed junction boxes or on direct mounts to the wall with feed thru 1/2" conduit access.

REFLECTOR & COVER:

- Anodized specular aluminum reflector with high efficiency and wide beam spread.
- Heat and impact resistant tempered clear prismatic glass lens.

LAMP:

- Compact fluorescent lamp GX24q base, 4-pin, single lamp option.
- HID lamps will have medium base (E26) porcelain socket with screw shell and center contact.
- Lamp included.

ELECTRICAL:

- The compact fluorescent lamps use a multi-voltage (120-277V) electronic high power factor ballast with ambient operating temperature of -20°F (-30°C) system.
- MH ballasts are standard high power factor ballast with ambient operating temperature of -20°F (-30°C) to 108°F (90°C); 180°C insulation system.
- HPS ballasts are standard high power factor ballast with ambient operating temperature of -40°F (-40°C); 180°C insulation system.

LISTING:

- UL/CUL listed.
- Suitable for wet location.
- ARRA compliant (optional)

DISCONTINUED


CWP2 CWP2L






CWP2

CWP2L





Specifications: CWP2

Height: 8-7/8 (226) Width: 8-7/16 (215) Depth: 7-1/8 (180)

Specifications: CWP2L

Height: 9-1/4 (235) Width: 9 (229) Depth: 7-7/8 (200)

All dimensions are in inches (millimeters).

LAMP CONFIGURATIONS					
CWP2	M50, H50, H70, H100 M70, M100 142	120V QT UNV			
CWP2L	M70, M100 H70, H100, H150 142	QT QT UNV			

ORDERING INFORMATION

EXAMPLE: CWP2-M70-QT-BZ

MODEL	LAMP TYPE		LAMP SOURCE		VOLTAGE	
CWP2 CWP2L	M50 M70 M100 H50 H70 H100 H150	50W Metal Halide 70W Metal Halide 100W Metal Halide 50W High Pressure Sodium 70W High Pressure Sodium 100W High Pressure Sodium 150W High Pressure Sodium (1) CF42 TRT, 4-Pin	(Blank) PS	Standard Pulse Start ²	120 208 240 277 QT UNV	120V 208V 240V 277V 120/208/240/277V 120-277V ³

FINISH		OPTIONS		
BZ WH BK	Dark Bronze (Std.) White Black Available custom color (RAL) Please provide us with the RAL number.	F1 F2 PC1 PC2 ARRA	Single Fuse (120, 277 or 347V only) ³ Double Fuse (208, 240 or 480V only) ³ With Photocell - Button Type 120V With Photocell - Button Type 277V Assembled in USA for Buy American Act	

NOTES:

- 1. 120V only.
 2. Pulse start MH available on 70 and 100 only.
- 3. Multi-voltage ballast for compact fluorescent (120-277V).
- 4. Must specify voltage.