

FLPL50-F-2G

Project Name:	
Type:	



FEATURES:

- Aluminum housing with frame.
- Non-toxic, non-radioactive, and recyclable aluminum.
- 50 feet viewing distance.
- Aluminum panel background with photoluminescent yellowish surface printed letter available in Red, Green, or Black panel.
- Single or double sided (two same-colored side panels).
- Two self-adhesive chevron stickers are included in case the directional chevron(s) is required.
- Need at least 5 foot candle of fluorescent illumination on the face of the sign at all times.

MOUNTING:

- Accessories for flat wall mount included as standard.
- Optional: ceiling or perpendicular (side wall) flag mount.

LISTING:


- Listed to Standard UL924 by ETL Intertek Testing.
- IBC and IFC codes compliant.
- OSHA and NFPA 101-Life Safety Code compliant.
- Listed for high-location and floor-proximity installation, impact resistant.



Specifications: FLPL50-F-2G

Tall: 10-1/4 (260)
Wide: 18-3/4 (476)

All dimensions are in inches (millimeters).



1.5B : 1.5" away from Ceiling or Side wall.
10B : 10" away from the Ceiling.
19.5B : 19.5" away from the Ceiling.

ORDERING INFORMATION

EXAMPLE: FLPL50-F-2G-S-R

MODEL	# OF FACE	PANEL COLOR	MOUNTING BRACKET
FLPL50-F-2G	S Single	R Red panel with yellow letter	1.5B Mounting bracket 1.5" away from ceiling or side wall (flag mount)
	D Double ¹	G Green panel with yellow letter	10B Extended mounting bracket 10" away from ceiling mount
		B Black panel with yellow letter	19.5B Extended mounting bracket 19.5" away from ceiling mount

NOTES:

1. Two same-colored side panels.