



Discontinued - limited stock available

APPLICATION

The half round wall sconce down light is ideal for walkways, building exterior walls, parking areas, entrances, underpasses, loading docks and recreation areas. Wall mounting height requires between 8 feet and 15 feet below.

FEATURES:

- Full cut-off dark sky compliant fixtures.
- Heavy duty die-cast aluminum housing on which electrical components are mounted for maximum heat dissipation.
- Silicone rubber gasket between backplate and front cover for wet locations.
- Architectural dark bronze finish as standard. Also available in white or black finish.
- One piece high reflectance aluminum reflector designed for desired light efficiency.
- Suitable for building surface and wall mounted applications.
- Provide down light only.

MOUNTING:

- Wall mounting only.
- Easily installed on recessed junction boxes or direct mounts to the wall with feed thru conduit access.

REFLECTOR & COVER:

- High efficiency anodized aluminum reflector with wide beam spread.
- Heat and impact resistant tempered clear glass lens.

LAMP:

- HID lamps have medium base (E26) porcelain socket with screw shell and center contact. UL certified socket.
- Compact fluorescent lamps have 4-pin socket (GX24).
- Lamp included.

LED OPTION:



- Requires longer lead time.
- CREE XPG LED (130 lm/pcs).
- 33LED (50W, Min. 3800 Lumen).

ELECTRICAL:

- MH ballasts are standard high power factor ballast with ambient operating temperature of -20°F (-30°C) to 108°F (90°C); 180°C insulation system.
- HPS ballasts are standard high power factor ballast with ambient operating temperature of -40°F (-40°C); 180°C insulation system.
- Compact fluorescent uses a high power factor electronic ballast, multi-voltage (120-277V), sound rate A, thermoplastic sockets.

LISTING:

- UL/CUL listed.
- Suitable for wet location.
- ARRA compliant (optional).



Specifications: UDL4

Height: 9-11/16 (245)
Width: 14-3/8 (366)
Depth: 9-1/4 (235)

All dimensions are in inches (millimeters).

ORDERING INFORMATION

EXAMPLE: UDL4-M175-QT-BZ

MODEL		LAMP TYPE				BALLAST	
UDL4	M50	50W Metal Halide	126T	(1) CF26 TRT, 4-Pin	(Blank)	Standard Pulse Start ³	
	M70	70W Metal Halide	226T	(2) CF26 TRT, 4-Pin			
	M100	100W Metal Halide	132T	(1) CF32 TRT, 4-Pin			
	M150	150W Metal Halide	232T	(2) CF32 TRT, 4-Pin			
	M175	175W Metal Halide	142T	(1) CF42 TRT, 4-Pin			
				242T	(2) CF42 TRT, 4-Pin	PS SCWA Super CWA Pulse Start Ballast ⁴	
		H50	50W High Pressure Sodium ¹	33LED	50W LED Input Power ² 5000K Color Temperature (Std.)		
		H70	70W High Pressure Sodium				
		H100	100W High Pressure Sodium				
		H150	150W High Pressure Sodium				
VOLTAGE		FINISH		OPTIONS			
120	120V	BZ WH BK	Dark Bronze (Std.) White Black	F1	Single Fuse (120, 277 or 347V only) ⁵		
208	208V			F2	Double Fuse (208, 240 or 480V only) ⁵		
240	240V			PC1	With Photocell - Button Type 120V		
277	277V			PC2	With Photocell - Button Type 277V		
QT	120/208/240/277V	Available custom color (RAL) Please provide us with the RAL number.		EM	Emergency Ballast ⁶		
UNV	120-277V ²			ARRA	Assembled in USA for Buy American Act		

NOTES:

1. 120V only.
2. Multi-voltage for compact fluorescent and LED (120-277V).
3. Pulse start metal halide available on 70, 100, 150 and 175 only.
4. Super CWA available on 150 and 175 only.

5. Must specify voltage.
6. Only for compact fluorescent unit. (Emergency Ballast options, see page 79).