
DISCONTINUED Limited Stock Available





The premium vandal resistant outdoor luminaires for general illumination in rough service, vandal resistant, ideal for commercial and residential applications. Use on entrances, walkways, building wall mount, where safety and security areas.






Specifications:

Height: 4-1/4 (108) Diameter: 13 (330)

All dimensions are in inches (millimeters).





Specifications:

Height: 4-1/4 (108), 5 (127) Diameter: 10-1/2 (266.7)

All dimensions are in inches (millimeters).

FXAMPI F. VOR2-2-18-UNV-B7

LAMP CONFIGURATIONS					
MODEL	# OF LAMPS	LAMP TYPE			
VOR2	2	CF13, CF18, CF26			
VOR4	1 2	CF13, CF18, CF26 CF13			

OPPEDING INFORMATION

ONDERING IN ORMATION				EXCUSION EL. VOITE E 10 014V BZ				
MODE	# OF LAMPS	LAMP TYPE		VOLTAGE		FINISH		
13" Diameter VOR2 10-1/2" Diameter VOR4	2	13 18 26 26T	CF13 DTT, 4-Pin CF18 DTT, 4-Pin CF26 DTT, 4-Pin CF26 TRT, 4-Pin	120 277 UNV	120V 277V 120-277V (Std.)	BK WH BZ	Black (Std.) White Dark Bronze	

OPTIONS										
F1 F2 PC1 PC2	Single Fuse (120, 277 or 347V only) ¹ Double Fuse (208, 240 or 480V only) ¹ With Photocell - Button Type 120V With Photocell - Button Type 277V				EM TR RRA	Tamp	rgency Ballast ^{2,3} per resistant screw mbled in USA for E			

NOTES:

- Must specify voltage.
 13" Diameter, 1 lamp only.
- Only for compact fluorescent unit. (Emergency Ballast options, see page 79).
- 3. Available with 1 lamp only.

FEATURES:

- Large round 13" diameter and 10-1/2" diameter die-cast aluminum premium vandal resistant bulkhead lighting. 2-pieces die-cast aluminum housing.
- Available in white or black powder coated finish.
- Smooth exterior, injection-molded and UV stabilized white polycarbonate diffuser.
- Hexagon socket head stainless steel bolt fasteners.
- Housing has one-piece silicone "O" ring. Fully gasket to seal to housing.
- High gloss white powder coat finish reflector.
- Photocell, tamper proof screws and emergency battery pack optional. (13" diameter 1 lamp only)

MOUNTING:

- Wall or ceiling surface mounting.
- Easily installs on recessed junction boxes or conduit entry.
- Mounting hardware included.

LAMP:

- Compact fluorescent 13W, 18W and 26W 4-pin double twin tube lamps.
- Lamp included.

ELECTRICAL:

Compact fluorescent ballast operate from 50/60Hz input source of 120V through 277V, electronic programmed start, high power factor ballast with minimum start operating temperature of 0°F (-18°C), THD of less than 10%, class A sound rating, class P and type 1 outdoor.

LISTING:

- ETL listed.
- Suitable for wet location.
- ARRA compliant (optional).

WARRANTY:

2-years limited warranty.